



## PORTABLE GASOLINE GENSET

### Continuous Power

The maximum power which a generating set is capable of delivering continuously whilst supplying a constant electrical load. Average load can be 100%. The generator must not be overloaded.

### Standby Power

The maxpower available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utilitypower outage or under test conditions for up to 200 hrs of operation per year under average of 70%load.Overloading isn't permissible.

### Prime Power

The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.

### Genset

Standby	kVA	15
Prime	kVA	13,6
Start System		Electric Start
Power Factor	CosΦ	1.0
Voltage		220(50HZ)
Fuel Type		Gasoline
Fuel Tank Capacity	lt	50

### Engine

Model		2V80-2
Kw (Standby/Prime)		13 / 12
Bore / Stroke	mm	80 x 74
Number of Cylinder / Type		2 / V Type
Displacement	cc	744
Oil Capacity	lt	1,6
Engine Type		4-Stroke, Air Cooled,OHV

### Size

Weight	kg	172
L x W x H	cm	81x 67 x 82